

SAFETY DATA SHEET

Acid Gas

Section 1. Identification

Product name : Acid Gas
Product code : Not available.
Synonyms : SWS Gas, Sour Water Stripper Gas, Amine Off Gas, SRU Gas

Relevant identified uses of the substance or mixture and uses advised against

Product use : Intermediate.
Area of application : Industrial applications.

Manufacturer : HollyFrontier Refining & Marketing LLC
2828 North Harwood
Suite 1300
Dallas, Texas 75201
USA
Customer Service: 1-214-954-6720

e-mail address of person responsible for this SDS : hfcsds@hollyfrontier.com
Emergency telephone number : CHEMTREC® (800) 424-9300
CCN 201319

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : H220 FLAMMABLE GASES - Category 1
H280 GASES UNDER PRESSURE - Compressed gas
H331 ACUTE TOXICITY (inhalation) - Category 3
H315 SKIN IRRITATION - Category 2
H319 EYE IRRITATION - Category 2A
H336 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
H373 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H220 - Extremely flammable gas.
H280 - Contains gas under pressure; may explode if heated.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H331 - Toxic if inhaled.
H336 - May cause drowsiness or dizziness.
H373 - May cause damage to organs through prolonged or repeated exposure. (lungs)

Precautionary statements

Prevention	: Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Do not breathe gas. Wash thoroughly after handling.
Response	: Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Get medical advice or attention if you feel unwell. In case of leakage, eliminate all ignition sources. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	: Protect from sunlight. Store in a well-ventilated place.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Keep container tightly closed. Do not breathe gas. Use only with adequate ventilation.
Hazards not otherwise classified	: Causes respiratory tract burns.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	Other names	%	CAS number
Hydrogen sulphide	-	30 - 65	7783-06-4
Carbon dioxide, gas	-	10 - 35	124-38-9
Hydrocarbons C1-7	-	1 - 3	-
ammonia, anhydrous	-	0 - 3	7664-41-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention. Continue to rinse for at least 15 minutes.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. To avoid the risk of static discharges and gas ignition, soak contaminated clothing thoroughly with water before removing it. Continue to rinse for at least 15 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: As this product is a gas, refer to the inhalation section.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation. Contact with rapidly expanding gas may cause burns or frostbite.
- Inhalation** : Toxic if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. Corrosive to the respiratory system.
- Skin contact** : Causes skin irritation. Contact with rapidly expanding gas may cause burns or frostbite.
- Ingestion** : May cause burns to mouth, throat and stomach. Can cause central nervous system (CNS) depression. As this product is a gas, refer to the inhalation section.

Over-exposure signs/symptoms

- Eye contact** : pain or irritation; watering; redness
- Inhalation** : respiratory tract irritation; coughing; nausea or vomiting; headache; heartbeat irregularity (arrhythmia); drowsiness/fatigue; dizziness/vertigo; loss of smell; respiratory paralysis; unconsciousness
- Skin contact** : irritation; redness
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of medical responders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : Do not use water jet.

Specific hazards arising from the chemical

- : Contains gas under pressure. Extremely flammable gas. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

Hazardous thermal decomposition products

- : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
sulfur oxides

Special protective actions for fire-fighters

- : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Contact supplier immediately for specialist advice. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. If involved in fire, shut off flow immediately if it can be done without risk. If this is impossible, withdraw from area and allow fire to burn. Fight fire from protected location or maximum possible distance. Eliminate all ignition sources if safe to do so.

Special protective equipment for fire-fighters

- : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : Accidental releases pose a serious fire or explosion hazard. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe gas. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- Environmental precautions** : Ensure emergency procedures to deal with accidental gas releases are in place to avoid contamination of the environment. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment.
- Large spill** : Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Contains gas under pressure. Do not get in eyes or on skin or clothing. Do not breathe gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not puncture or incinerate container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Eliminate all ignition sources. Keep container tightly closed and sealed until ready for use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Hydrogen sulphide	<p>ACGIH TLV (United States, 3/2020). TWA: 1 ppm 8 hours. STEL: 5 ppm 15 minutes.</p> <p>OSHA PEL Z2 (United States, 2/2013). CEIL: 20 ppm AMP: 50 ppm 10 minutes.</p> <p>NIOSH REL (United States, 10/2016). CEIL: 10 ppm 10 minutes. CEIL: 15 mg/m³ 10 minutes.</p>
Carbon dioxide, gas	<p>ACGIH TLV (United States, 3/2020). TWA: 5000 ppm 8 hours. TWA: 9000 mg/m³ 8 hours. STEL: 30000 ppm 15 minutes. STEL: 54000 mg/m³ 15 minutes.</p> <p>NIOSH REL (United States, 10/2016). TWA: 5000 ppm 10 hours. TWA: 9000 mg/m³ 10 hours. STEL: 30000 ppm 15 minutes. STEL: 54000 mg/m³ 15 minutes.</p> <p>OSHA PEL (United States, 5/2018). TWA: 5000 ppm 8 hours. TWA: 9000 mg/m³ 8 hours.</p>
Hydrocarbons C1-7 ammonia, anhydrous	<p>None.</p> <p>ACGIH TLV (United States, 3/2020). TWA: 25 ppm 8 hours. TWA: 17 mg/m³ 8 hours. STEL: 35 ppm 15 minutes. STEL: 24 mg/m³ 15 minutes.</p> <p>NIOSH REL (United States, 10/2016). TWA: 25 ppm 10 hours. TWA: 18 mg/m³ 10 hours. STEL: 35 ppm 15 minutes. STEL: 27 mg/m³ 15 minutes.</p> <p>OSHA PEL (United States, 5/2018). TWA: 50 ppm 8 hours. TWA: 35 mg/m³ 8 hours.</p>

Appropriate engineering controls

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

- Physical state** : Gas.
- Color** : Colorless.
- Odor** : Rotten eggs./Sulfurous.
- Odor threshold** : Not available.
- pH** : Not applicable.
- Melting point** : -68°C (-90°F)
- Boiling point, initial boiling point, and boiling range** : -61°C (-78°F)
- Flash point** : <-12°C (<10°F)
- Evaporation rate** : Not available.
- Flammability** : Not available.
- Lower and upper explosion limit/flammability limit** : Lower: 3%
Upper: 44%
- Vapor pressure** : Not available.
- Relative vapor density** : >1 [Air = 1]
- Relative density** : Not applicable.
- Density** : Not applicable.
- Solubility** : Very slightly soluble in the following materials: cold water and hot water.
- Partition coefficient: n-octanol/water** : Not applicable.
- Auto-ignition temperature** : 260°C (500°F)
- Decomposition temperature** : Not available.
- SADT** : Not available.
- Viscosity** : Not applicable.
- Flow time (ISO 2431)** : Not available.
- Particle characteristics**
- Median particle size** : Not applicable.
- Additional information**

Physical/chemical properties comments : No additional information.

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.
Under normal conditions of storage and use, hazardous polymerization will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

Incompatible materials : No specific data.

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Hydrogen sulphide ammonia, anhydrous	LC50 Inhalation Gas.	Rat	444 ppm	4 hours
	LC50 Inhalation Gas.	Rat	9500 ppm	1 hours
	LC50 Inhalation Gas.	Rat	2000 ppm	4 hours

Irritation/Corrosion

Not available.

Conclusion/Summary

Skin : Causes skin irritation.
Eyes : Causes serious eye irritation.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Hydrogen sulphide	Category 3	-	Respiratory tract irritation Narcotic effects
	Category 3		

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Hydrogen sulphide	Category 2	inhalation	lungs

Aspiration hazard

Not available.

Information on the likely routes of exposure : Routes of entry anticipated: Oral, Dermal, Inhalation.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

General : May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity**Acute toxicity estimates**

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Acid Gas	N/A	N/A	700.8	N/A	N/A
hydrogen sulphide	N/A	N/A	444	N/A	N/A
ammonia, anhydrous	N/A	N/A	2000	N/A	N/A

Section 12. Ecological information**Toxicity**

Product/ingredient name	Result	Species	Exposure
hydrogen sulphide	Acute EC50 62 µg/l Fresh water	Crustaceans - Gammarus pseudolimnaeus	2 days
	Acute LC50 2 µg/l Fresh water	Fish - Coregonus clupeaformis - Yolk-sac fry	96 hours
ammonia, anhydrous	Acute EC50 29.2 mg/l Marine water	Algae - Ulva fasciata - Zoea	96 hours
	Acute LC50 2080 µg/l Fresh water	Crustaceans - Gammarus pulex	48 hours
	Acute LC50 0.53 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 300 µg/l Fresh water	Fish - Hypophthalmichthys nobilis	96 hours
	Chronic NOEC 0.204 mg/l Marine water	Fish - Dicentrarchus labrax	62 days

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Carbon dioxide, gas	0.83	-	low
ammonia, anhydrous	0.0724	-	low

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.




Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Empty pressure vessels should be returned to the supplier. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

United States - RCRA Toxic hazardous waste "U" List

Ingredient	CAS #	Status	Reference number
Hydrogen sulfide; Hydrogen sulfide H2S	7783-06-4	Listed	U135

Section 14. Transport information

	DOT Classification	IMDG	IATA
UN number	UN1953	UN1953	UN1953
UN proper shipping name	Compressed gas, toxic, flammable, n.o.s. (hydrogen sulphide, ammonia, anhydrous)	COMPRESSED GAS, TOXIC, FLAMMABLE, N.O.S. (hydrogen sulphide, ammonia, anhydrous)	Compressed gas, toxic, flammable, n.o.s. (hydrogen sulphide, ammonia, anhydrous)
Transport hazard class(es)	2.3 (2.1) 	2.3 (2.1) 	2.3 (2.1) 
Packing group	-	-	-
Environmental hazards	No.	Yes.	Yes. The environmentally hazardous substance mark is not required.

Additional information

DOT Classification

: Toxic - Inhalation hazard Zone C
Reportable quantity 210.53 lbs / 95.579 kg. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.
Limited quantity No.
Packaging instruction Exceptions: None. Non-bulk: 302, 305. Bulk: 314, 315.
Quantity limitation Passenger aircraft/rail: Forbidden. Cargo aircraft: Forbidden.
Special provisions 3, B14

IMDG

: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
Emergency schedules F-D, S-U
Special provisions 274
IMDG Code Segregation group SGG18 - Alkalis

IATA : The environmentally hazardous substance mark may appear if required by other transportation regulations.
Quantity limitation Passenger and Cargo Aircraft: Forbidden. Packaging instructions: Forbidden. Cargo Aircraft Only: Forbidden. Packaging instructions: Forbidden. Limited Quantities - Passenger Aircraft: Forbidden. Packaging instructions: Forbidden.
Special provisions A2

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

U.S. Federal regulations : **United States inventory (TSCA 8b):** Not determined.
Clean Water Act (CWA) 311: hydrogen sulphide; ammonia, anhydrous
Clean Air Act (CAA) 112 regulated toxic substances: hydrogen sulphide; ammonia, anhydrous

RCRA (Resource Conservation and Recovery Act) Hazardous waste constituents appendix VIII to 40 CFR part 261

Name	%	Status
Hydrogen sulphide	30 - 65	Listed

Department of homeland security (DHS), Chemical Facility Anti-terrorism Standards (6 CFR 27), Appendix A, Chemicals of Interest

	Name	%	Status
Release	Hydrogen sulphide	30 - 65	Listed
	ammonia, anhydrous	0 - 3	Listed
Theft	Hydrogen sulphide	30 - 65	Listed
Security	Hydrogen sulphide	30 - 65	Listed
	ammonia, anhydrous	0 - 3	Listed

SARA 302/304

Composition/information on ingredients

Name	%	EHS	SARA 302 TPQ		SARA 304 RQ	
			(lbs)	(gallons)	(lbs)	(gallons)
Hydrogen sulphide	30 - 65	Yes.	500	-	100	-
ammonia, anhydrous	0 - 3	Yes.	500	-	100	-

SARA 304 RQ : 210.5 lbs / 95.6 kg

SARA 311/312

Classification : **FLAMMABLE GASES** - Category 1
GASES UNDER PRESSURE - Compressed gas
ACUTE TOXICITY (inhalation) - Category 3
SKIN IRRITATION - Category 2
EYE IRRITATION - Category 2A
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
HNOC - Corrosive to respiratory tract

Composition/information on ingredients

Name	%	Classification
hydrogen sulphide	30 - 65	FLAMMABLE GASES - Category 1 GASES UNDER PRESSURE - Compressed gas ACUTE TOXICITY (inhalation) - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
Carbon dioxide, gas	10 - 35	GASES UNDER PRESSURE - Compressed gas SIMPLE ASPHYXIANTS
ammonia, anhydrous	0 - 3	FLAMMABLE GASES - Category 2 GASES UNDER PRESSURE - Compressed gas ACUTE TOXICITY (inhalation) - Category 3 SKIN CORROSION - Category 1B SERIOUS EYE DAMAGE - Category 1 HNOC - Corrosive to digestive tract HNOC - Corrosive to respiratory tract

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	hydrogen sulphide	7783-06-4	30 - 65
	ammonia, anhydrous	7664-41-7	0 - 3
Supplier notification	hydrogen sulphide	7783-06-4	30 - 65
	ammonia, anhydrous	7664-41-7	0 - 3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

- Massachusetts** : The following components are listed: HYDROGEN SULFIDE; CARBON DIOXIDE; AMMONIA; AMMONIA, ANHYDROUS
- New York** : The following components are listed: Hydrogen sulfide; Hydrosulfuric acid; Ammonia
- New Jersey** : The following components are listed: HYDROGEN SULFIDE; CARBON DIOXIDE; CARBONIC ACID GAS; AMMONIA
- Pennsylvania** : The following components are listed: HYDROGEN SULFIDE; CARBON DIOXIDE; AMMONIA

California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

International regulations**Chemical Weapon Convention List Schedules I, II & III Chemicals**

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia : Not determined.

Canada	: Not determined.
China	: Not determined.
Europe	: Not determined.
Japan	: Japan inventory (CSCL) : Not determined. Japan inventory (ISHL) : Not determined.
Malaysia	: Not determined
New Zealand	: Not determined.
Philippines	: Not determined.
Republic of Korea	: Not determined.
Taiwan	: Not determined.
Turkey	: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	3
Flammability	4
Physical hazards	3

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



Procedure used to derive the classification

Classification	Justification
FLAMMABLE GASES - Category 1 GASES UNDER PRESSURE - Compressed gas ACUTE TOXICITY (inhalation) - Category 3 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	On basis of test data On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method

Date of issue/Date of revision	: 08/24/2021
Date of previous issue	: 03/22/2018
Version	: 3

Key to abbreviations

: ATE = Acute Toxicity Estimate
AMP = Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
N/A = Not available
UN = United Nations

▣ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named manufacturer, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.